

MLFB-Ordering data

6FC5203-0AF01-0AA0



Figure similar

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Screen

Screen diagonal 10.4 in TFT color VGA

Screen resolution 640 x 480 Pixel

Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Rated data

Input voltage DC 5 V

Via PCU or TCU

Ambient temperature

Operation on the front 0 ... 45 °C (32 ... 113 °F)

Operation at the rear 0 ... 55 °C (32 ... 131 °F)

Storage -20 ... 55 °C (-4 ... 131 °F)

Transport -20 ... 55 °C (-4 ... 131 °F)

Power consumption

Maximum 16.0 W

Standard 10.0 W

Relative humidity

Operation 5 ... 95 %

Storage 5 ... 95 %

Transport 5 ... 95 %

Mechanical data

Net weight 5.0 kg (11.02 lb)

Width 483.0 mm (19.02 in)

Height 310.0 mm (12.20 in)

Depth 30.0 mm (1.18 in)
Without USB protective cover on the front

Installation depth 20.0 mm (0.79 in)

with PCU 50 101.0 mm (3.98 in)
Clearance + 10 mm (0.39 in)

Approvals

Certificate of suitability CE / cULus

Mounting surface

Cutout width 450.0 mm (17.72 in)

Cutout height 290.0 mm (11.42 in)

Degree of protection

Front side IP54

Rear side IP00